


Mobile manipulator for research and education




www.youbot-store.com

KEY FEATURES:

- omnidirectional mobile platform
- 5-DOF manipulator
- two-finger gripper
- real-time EtherCAT communication
- open interfaces
- arm and platform can be used independently





General characteristics youBot arm		
Serial kinematics	5 axes	
Height	655 mm	
Work envelope	0.513 m³	
Weight	6.3 kg	
Payload	0.5 kg	
Structure	Magnesium Cast	
Positioning repeatability	1 mm	
Communication	EtherCAT	
Voltage connection	24 V DC	
Drive train power limitable to	80 W	
Axis data	Range	Speed
A 1 4 (A4)		
Axis 1 (A1)	+/- 169°	90 °/s
Axis 2 (A2)	+/- 169° + 90°/- 65°	90 °/s
Axis 2 (A2)	+ 90°/- 65°	90 °/s
Axis 2 (A2) Axis 3 (A3)	+ 90°/- 65° + 146°/- 151°	90 °/s 90 °/s
Axis 2 (A2) Axis 3 (A3) Axis 4 (A4)	+ 90°/- 65° + 146°/- 151° +/- 102°	90 °/s 90 °/s 90 °/s 90 °/s
Axis 2 (A2) Axis 3 (A3) Axis 4 (A4) Axis 5 (A5)	+ 90°/- 65° + 146°/- 151° +/- 102° +/- 167°	90 °/s 90 °/s 90 °/s 90 °/s

General characteristics youBot platform	
Omnidirectional kinematics	4 KUKA omniWheels
Length	580 mm
Width	380 mm
Height	140 mm
Clearance	20 mm
Weight	20 kg
Payload	20 kg
Structure	Steel
Speed	0.8 m/s
Communication	EtherCAT
Voltage connection	24 V DC

General characteristics energy supply
Maintenance-free lead acid rechargeable batteries: 24 V, 5 Ah; Power supply: 200 W
Approximate battery runtime of KUKA youBot mobile manipulator: 90 minutes
General characteristics mini PC
Mini ITX PC-Board with embedded Intel® Atom Dual-Core CPU, 2 GB RAM, 32 GB SSD, USB

Disclaimer Specifications regarding the quality and usability of the products do not constitute a warranty of properties. They are intended to serve informative purposes only. Solely the respective contract of sale is binding with respect to the supplied goods and services.



FREE SOFTWARE AVAILABLE:

- Linux installation
- Open source robot controller with open interfaces (position, velocity and current control)
- BRIDE (BRICS Integrated Development Environment) based on Eclipse to simplify application development
- BROCRE (BRICS Open Code Repository) offers
 - interoperable interfaces and
 - best practice algorithms libraries:
 - BRICS_MM: mobile manipulation
 - BRICS_3D: 3D perception and modelling
- BRICS_RN: robust navigation
 Blender simulation model
- Sample applications

KUKA

Further information available at:

www.youbot-store.com